

RED-EMC Test Report

Client Name : Jinan USR IOT Technology Limited

Address : Room 203, 205, 208. Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, 250101, China

Product Name : Industrial 4G Modem

Date : May 20, 2019

Shenzhen Anbotech Compliance Laboratory Limited

Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Modes.....	6
1.5. Test Equipment List.....	8
1.6. Description of Test Facility.....	11
1.7. Performance Criteria.....	11
2. Summary of Test Results.....	15
3. Emission Test.....	16
3.1. Conducted Emission Test at Main Ports.....	16
3.1.1. Test Standard and Limit.....	16
3.1.2. Test Setup.....	17
3.1.3. Test Procedure.....	17
3.1.4. Test Data.....	17
3.2. Radiated Emission Test.....	22
3.2.1. Test Standard and Limit.....	22
3.2.2. Test Setup.....	23
3.2.3. Test Procedure.....	23
3.2.4. Test Data.....	24
3.3. Harmonic Current Emissions.....	30
3.3.1. Test Standard and Limit.....	30
3.3.2. Test Setup.....	30
3.3.3. Test Procedure.....	30
3.3.4. Test Data.....	31
3.4. Voltage Fluctuations and Flicker.....	32
3.4.1. Test Standard and Limit.....	32
3.4.2. Test Setup.....	32
3.4.3. Test Procedure.....	32
3.4.4. Test Data.....	33
4. Immunity Test.....	36
4.1. Electrostatic Discharge Test.....	37
4.1.1. Test Standard and Specification.....	37
4.1.2. Test Setup.....	37
4.1.3. Test Procedure.....	38
4.1.4. Test Data.....	38
4.2. Radiated, RF Electromagnetic Fields Test.....	40
4.2.1. Test Standard and Specification.....	40
4.2.2. Test Setup.....	40



4.2.3. Test Procedure.....	40
4.2.4. Test Data.....	41
4.3. Fast Transients, Common Mode Test.....	45
4.3.1. Test Standard and Specification.....	45
4.3.2. Test Setup.....	45
4.3.3. Test Procedure.....	45
4.3.4. Test Data.....	46
4.4. Surges Test.....	47
4.4.1. Test Standard and Specification.....	47
4.4.2. Test Setup.....	47
4.4.3. Test Procedure.....	47
4.4.4. Test Data.....	48
4.5. Radio Frequency, Common Mode Test.....	50
4.5.1. Test Standard and Specification.....	50
4.5.2. Test Setup.....	50
4.5.3. Test Procedure.....	50
4.5.4. Test Data.....	51
4.6. Voltage Dips and Interruptions.....	54
4.6.1. Test Standard and Specification.....	54
4.6.2. Test Setup.....	54
4.6.3. Test Procedure.....	54
4.6.4. Test Data.....	55
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	56
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	61
APPENDIX III -- INTERNAL PHOTOGRAPH.....	66



TEST REPORT

Applicant : Jinan USR IOT Technology Limited
Manufacturer : Jinan USR IOT Technology Limited
Product Name : Industrial 4G Modem
Model No. : USR-G781, USR-G806, USR-G800 V2, USR-G808, USR-G809, USR-G810,
USR-G811, GW-R4513, GW-R5514, GW-R731
Trade Mark : 
Rating(s) : Input: DC 9-12V, 300mA Max
Test Standard(s) : ETSI EN 301 489-1 V2.1.1 (2017-02)
ETSI EN 301 489-52 V1.1.0 (2016-11)
EN 55032: 2015
EN 55035: 2017

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the EN 301 489-1 & EN 301 489-52 ,EN 55032 and EN 55035 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Apr. 02, 2019

Date of Test


Apr. 02~ May 16, 2019

Prepared By



(Engineer / Oliay Yang)

Reviewer



(Supervisor / Snowy Meng)

Approved & Authorized Signer




(Manager / Sally Zhang)

1. General Information

1.1. Client Information

Applicant	:	Jinan USR IOT Technology Limited
Address	:	Room 203, 205, 208. Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, 250101, China
Manufacturer	:	Jinan USR IOT Technology Limited
Address	:	Room 203, 205, 208. Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, 250101, China
Factory	:	Jinan USR IOT Technology Limited
Address	:	Room 203, 205, 208. Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, 250101, China

1.2. Description of Device (EUT)

Product Name	:	Industrial 4G Modem
Model No.	:	USR-G781, USR-G806, USR-G800 V2, USR-G808, USR-G809, USR-G810, USR-G811, GW-R4513, GW-R5514, GW-R731 (Note: All samples are the same except the name, so we prepare "USR-G781" for test only.)
Trade Mark	:	
Test Power Supply	:	AC 110V, 50Hz for adapter / AC 230V, 50Hz for adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Product Description	:	<div> <div>Operation Frequency:</div> <div> GSM 900: 880 -915 MHz (TX); 935 - 960 MHz (RX) DCS1800: 1710 -1785 MHz (TX); 1805-1880 MHz (RX) WCDMA2100:1922.6MHz-1977.4MHz WCDMA900:882.6MHz-912.4MHz LTE :FDD:Band1:TX:1920MHz~1980MHz, RX:2110MHz~2170MHz LTE :FDD:Band3:TX:1710MHz~1785MHz, RX:1805MHz~1880MHz LTE :FDD:Band8:TX:880MHz~915MHz, RX:925MHz~960MHz LTE :TDD: Band38:2570MHz~2620MHz LTE :TDD: Band40:2300MHz~2400MHz </div> </div> <div> <div>Modulation Type:</div> <div> GSM900/1800: GMSK,8PSK WCDMA900/2100:QPSK,16QAM </div> </div>

		LTE FDD:QPSK,16QAM
	Description test modes:	Only SIM 1 is a chipset unit and tested as single chipset, SIM 1 is used to tested.
	Antenna Type:	GSM900/1800: Sucker External Antenna WCDMA900/2100: Sucker External Antenna LTE Band 1/3/8/38/40: Sucker External Antenna
	Antenna Gain(Peak):	GSM 900: 1.74 dBi DCS1800: 2.42 dBi WCDMA900: 1.74 dBi WCDMA2100: 3.82 dBi LTE Band 1: 3.82 dBi LTE Band 3: 2.42 dBi LTE Band 8: 1.74 dBi LTE Band 38: 3 dBi LTE Band 40: 3 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Adapter	:	P/N:DQS151-120100-16312B Model:DQS151-120100-VV Input: AC 100-240V 50/60Hz 0.4A Max Output: DC 12.0V, 1.0A
---------	---	---

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	LAN Mode
Mode 2	GSM900 Mode
Mode 3	DCS1800 Mode

Mode 4	WCDMA Mode
Mode 5	LTE Mode

For Conducted Emission	
Final Test Mode	Description
Mode 1	LAN Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	LAN Mode
Mode 2	GSM900 Mode
Mode 3	DCS1800 Mode
Mode 4	WCDMA Mode
Mode 5	LTE Mode

1.5. Test Equipment List

Conducted Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 05, 2018	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 05, 2018	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 05, 2018	1 Year
4.	Software Name EZ-EMC	Ferrari Technology	ANB-03A	N/A	N/A	N/A
5.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 05, 2018	1 Year
2.	Pre-amplifier	Schwarzbeck	BBV-9745	9745-075	Nov. 05, 2018	1 Year
3.	Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	01109	Nov. 05, 2018	1 Year
4.	Software Name EZ-EMC	Ferrari Technology	EMEC-3A1	N/A	N/A	N/A
5.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Harmonic and Flicker Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Programmable AC Power source	IVYTECH	APS-5005A	632734	June 15, 2018	1 Year
2.	Harmonic and Flicker Analyzer	EMC-PARTNER	HRRMOINCS -1000-1P	164	Nov. 05, 2018	1 Year
3.	Harmonics-1000	N/A	Ed.3.0+4.0	N.A	N/A	N/A
4.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Electrostatic Discharge Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	ESD Simulators	3Ctest	ESD-30T	ES0131505	Nov. 05, 2018	1 Year
2.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Surge Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.1	6kV Surge Generator	TESEQ	NSG 3060	1480	Nov. 05, 2018	1 Year
1.2	CDN	TESEQ	CDN 3061	1408	Nov. 05, 2018	1 Year
2.1	6kV Surge Generator	EMPEK	LSG-5060G	06010017N	Nov. 05, 2018	1 Year
2.2	CDN	EMPEK	CDN-5110G	061100005N	Nov. 05, 2018	1 Year
2.3	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

R/S Immunity Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Signal Generator	Agilent	N5182A	MY48180656	Nov. 05, 2018	1 Year
2	Amplifier	Amplifier Research	150W1000M3	309410	N/A	N/A
3	Amplifier	Amplifier Research	60S1G3	309433	N/A	N/A
4	Log-Periodic Antenna	Schwarzbeck	VULP9118E	00992	Aug. 17, 2018	3 Year
5	Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 19, 2018	3 Year
6	Power Sensor	Agilent	E9301A	MY41498906	Nov. 05, 2018	1 Year
7	Power Sensor	Agilent	E9301A	MY41498088	Nov. 05, 2018	1 Year
8	Power Meter	Agilent	E4419B	GB40202909	Nov. 05, 2018	1 Year
9	Field Probe	ETS-Lindgren	HI-6006	00212747	Apr. 20, 2017	3 Year
10	software	EMtrace	EM 3	N/A	N/A	N/A
11	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Injected Currents Susceptibility Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	C/S Conducted Immunity Test System	FRANKONIA	CIT-10	126A1196/2012	Nov. 05, 2018	1 Year
2.	CDN	FRANKONIA	CDN - M2+ M3	A2210178/2012	Nov. 05, 2018	1 Year
3.	6dB Attenuator	FRANKONIA	DAM 26W	1172202	Nov. 05, 2018	1 Year
4.	CIT-10	FRANKONIA	Version1.1.7	N/A	N.A	N/A
5.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

Voltage Dips and Interruptions Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	CYCLE SAG Simulator	PRIMA	DRP61011AG	PR12046234	Nov. 05, 2018	1 Year
2.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW 500	104209	Nov. 05, 2018	1 Year

1.6. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

1.7. Performance Criteria

1.7.1. For EMS Test:

- √ A: Normal performance within the specification limits;
- √ B: Temporary degradation or loss of function or performance which is self-recoverable;
- √ C: Temporary degradation or loss of function or performance which requires operator intervention or system reset;
- √ D: Degradation or loss of function which is not recoverable due to damage of equipment (components) or software, or loss of data

Note: The manufacturer's specification may define effects on the EUT which may be considered insignificant, and therefore acceptable.

This classification may be used as a guide in formulating performance criteria, by committees responsible for generic, product and product-family standards, or as a framework for the agreement on performance criteria between the manufacturer and the purchaser, for example where no suitable generic, product or product-family standard exists.



1.7.2. For EN 301 489-52:**1.7.2.1. GSM and DCS Performance Criteria**

The equipment shall meet the performance criteria specified in this clause and clauses 6.1.1 to 6.1.4, as appropriate.

Portable equipment intended for use whilst powered by the main battery of a vehicle shall additionally fulfil the applicable requirements set out in ETSI EN 301 489-1 [1], clauses 7.1 and 7.2 for mobile equipment.

Portable or mobile equipment powered by the AC mains shall additionally fulfil the applicable requirements of ETSI EN 301 489-1 [1], clauses 7.1 and 7.2 for radio and ancillary equipment for fixed use.

The establishment and maintenance of a communications link, the assessment of RXQUAL, and the assessment of the audio breakthrough by monitoring the speech output signal level, are used as performance criteria to ensure that all primary functions of the transmitter and receiver are evaluated during the immunity tests. In addition, the test shall also be performed in idle mode to ensure the transmitter does not unintentionally operate.

The maintenance of a communications link shall be assessed using an indicator which may be part of the test system or the EUT.

If an equipment is of a specialized nature, such that the performance criteria described in the following clauses are not appropriate, then the manufacturer shall declare, for inclusion in the test report, his own specification for an acceptable level of performance or degradation of performance during and/or after the immunity tests. The performance specification shall be included in the product description and documentation.

The performance criteria specified by the manufacturer shall give the same degree of immunity protection as called for in the following clauses.

Performance criteria for Continuous phenomena applied to Transmitters (CT)

A communication link shall be established at the start of the test, and maintained during the test, see clauses 4.2.3 and 4.2.4.

During the test, the uplink speech output level shall be at least 35 dB less than the previously recorded reference levels, when measured through an audio band pass filter of width 200 Hz, centred on 1 kHz (audio breakthrough check).

NOTE: When there is a high level background noise present the filter bandwidth can be reduced down to a minimum of 40 Hz.

At the conclusion of the test, the EUT shall operate as intended with no loss of user control functions or stored data, and the communication link shall have been maintained. In addition to confirming the above performance during a call, the test shall also be performed in idle mode, and the transmitter shall not unintentionally operate.

Performance criteria for Transient phenomena applied to Transmitters (TT)

A communications link shall be established at the start of the test, see appropriate clauses 4.2 to 4.2.4.



At the conclusion of each exposure the EUT shall operate with no user noticeable loss of the communication link. At the conclusion of the total test comprising the series of individual exposures, the EUT shall operate as intended with no loss of user control functions or stored data, as declared by the manufacturer, and the communication link shall have been maintained. In addition to confirming the above performance during a call, the test shall also be performed in idle mode, and the transmitter shall not unintentionally operate.

Performance criteria for Continuous phenomena applied to Receivers (CR)

A communications link shall be established at the start of the test, see appropriate clauses 4.2 to 4.2.6. During the test, the RXQUAL of the downlink shall not exceed the value of three, measured during each individual exposure in the test sequence.

During the test, the downlink speech output level shall be at least 35 dB less than the previously recorded reference levels, when measured through an audio band pass filter of width 200 Hz, centred on 1 kHz (audio breakthrough check).

NOTE: When there is a high level background noise present the filter bandwidth can be reduced down to a minimum of 40 Hz. At the conclusion of the test, the EUT shall operate as intended with no loss of user control functions or stored data, and the communication link shall have been maintained.

Performance criteria for Transient phenomena applied to Receivers (TR)

A communications link shall be established at the start of the test, see appropriate clauses 4.2. to 4.2.6. At the conclusion of each exposure the EUT shall operate with no user noticeable loss of the communication link. At the conclusion of the total test comprising the series of individual exposures, the EUT shall operate as intended with no loss of user control functions or stored data, as declared by the manufacturer, and the communication link shall have been maintained.

1.7.2.2. CDMA Direct Spread (UTRA and E-UTRA) Performance Criteria

The equipment shall meet the performance criteria specified in this clause and clauses 6.2.2 and 6.2.3 as appropriate.

The maintenance of a communications link shall be assessed by using an indicator, which may be part of the test system or the equipment under test. If an equipment is of a specialized nature, that the performance criteria described in the following clauses are not appropriate, then the manufacturer shall declare, for inclusion in the test report, his own specification for an acceptable level of performance or degradation of performance during and/or after testing, as required by the present document.

The performance criteria specified by the manufacturer shall give the same degree of immunity protection as called for in the following clauses. In addition, the test shall also be performed in idle mode to ensure the transmitter does not unintentionally operate. The requirements apply to all types of UTRA and E-UTRA (FDD or TDD) for the UE.

Performance criteria for continuous phenomena

A communication link shall be established at the start of the test, and maintained during the test, clauses 4.1 and 4.2. In the speech mode, the performance criteria shall be that the Up Link and Down Link speech output levels shall be at least 35 dB less than the recorded reference levels, when measured

through an audio band pass filter of width 200 Hz, centred on 1 kHz (annex B).

NOTE: When there is a high level of background audio noise present, the filter bandwidth can be reduced down to a minimum of 40 Hz. At the conclusion of the test, the EUT shall operate as intended with no loss of user control functions or stored data, and the communication link shall have been maintained. In addition to confirming the above performance in traffic mode, the test shall be performed in idle mode, and the transmitter shall not unintentionally operate.

UTRA

In the data transfer mode, the performance criteria can be one of the following:

- if the BER (as referred in ETSI TS 134 109 [4]) is used, it shall not exceed 0,001 during the test sequence;
- if the BLER (as referred in ETSI TS 134 109 [4]) is used, it shall not exceed 0,01 during the test sequence.

The BLER calculation shall be based on evaluating the CRC on each transport block.

E-UTRA

In the data transfer mode, the performance criteria shall be that the throughput shall be $\geq 95\%$ of the maximum throughput of the reference measurement channel as specified in annex C in ETSI TS 136 101 [9] with parameters specified in tables 7.3.1-1 and 7.3.1-2 in ETSI TS 136 101 [9] during the test sequence.

Performance criteria for Transient phenomena

A communications link shall be established at the start of the test, clauses 4.1 and 4.2.

At the conclusion of each exposure the EUT shall operate with no user noticeable loss of the communication link. At the conclusion of the total test comprising the series of individual exposures, the EUT shall operate as intended with no loss of user control functions or stored data, as declared by the manufacturer, and the communication link shall have been maintained. In addition to confirming the above performance in traffic mode, the test shall also be performed in idle mode, and the transmitter shall not unintentionally operate.

2. Summary of Test Results

EMC Emission				
Test Items	Standard	Basic Standard	Limit	Results
Conducted Emission	ETSI EN 301 489-1 V2.1.1 Clause 8.3 & 8.4	EN 55032: 2015	Class B	PASS
Radiated Emission	ETSI EN 301 489-1 V2.1.1 Clause 8.2	EN 55032: 2015	Class B	PASS
Harmonic Current Emission	ETSI EN 301 489-1 V2.1.1 Clause 8.5	EN 61000-3-2:2014	Class A	N/A
Voltage Fluctuations & Flicker	ETSI EN 301 489-1 V2.1.1 Clause 8.6	EN 6000-3-3:2013	/	PASS
EMC Immunity				
Test Items	Standard	Basic Standard	Performance Criteria	Results
Electrostatic Discharge	ETSI EN 301 489-1 V2.1.1 Clause 9.3	EN 61000-4-2:2009	B	PASS
RF Electromagnetic Field	ETSI EN 301 489-1 V2.1.1 Clause 9.2	EN 61000-4-3:2006 +A1:2008+A2:2010	A	PASS
Fast transients, common mode	ETSI EN 301 489-1 V2.1.1 Clause 9.4	EN 61000-4-4:2012	B	PASS
Surges	ETSI EN 301 489-1 V2.1.1 Clause 9.8	EN 61000-4-5:2014	B	PASS
Radio frequency, common mode	ETSI EN 301 489-1 V2.1.1 Clause 9.5	EN 61000-4-6:2014	A	PASS
Volt. Interruptions Volt. Dips	ETSI EN 301 489-1 V2.1.1 Clause 9.7	EN 61000-4-11:2004	B / C / C NOTE (3)	PASS
NOTE:				
	(1) "N/A" denotes test is not applicable in this Test Report			
	(2) Alternatively, for equipment intended to be used exclusively in an industrial environment or a telecommunication centre, the class A limits may be used.			
	(3) Voltage dip: 100% reduction – Performance Criteria B			
	Voltage dip: 100% reduction – Performance Criteria B			
	Voltage dip: 70% reduction – Performance Criteria C			
	Voltage Interruption: 0% Interruption – Performance Criteria C			

3. Emission Test

3.1. Conducted Emission Test at Main Ports

3.1.1. Test Standard and Limit

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 8.3 & 8.4
Basic Standard	EN 55032: 2015

Limits for conducted emissions


Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: *Decreasing linearly with logarithm of the frequency.

Limits for conducted emissions of equipment
intended to be used in telecommunication centres and industrial environment

Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	79	66
	500kHz~30MHz	73	60

3.1.2. Test Setup



3.1.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ETSI EN 301 489-1 V2.1.1 & EN55032: 2015 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

For the actual test configuration, please refer to the related Item EUT Test Photos.

3.1.4. Test Data


PASS

The EUT should be compliance to the limit of Class B

Only the worst case data was showed in the report, please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 230V, 50Hz for adapter
Comment: Live Line
Tem.: 22.8°C Hum.: 52%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2580	13.47	19.89	33.36	51.49	-18.13	AVG	
2	0.3820	24.92	19.93	44.85	58.23	-13.38	QP	
3	0.3820	15.67	19.93	35.60	48.23	-12.63	AVG	
4	0.4540	16.46	19.96	36.42	46.80	-10.38	AVG	
5	0.4580	23.59	19.96	43.55	56.73	-13.18	QP	
6	0.6460	10.06	20.02	30.08	46.00	-15.92	AVG	
7	0.7860	26.41	20.06	46.47	56.00	-9.53	QP	
8	1.3460	9.92	20.13	30.05	46.00	-15.95	AVG	
9	1.8220	23.93	20.14	44.07	56.00	-11.93	QP	
10	2.2620	8.90	20.15	29.05	46.00	-16.95	AVG	
11	2.5620	24.71	20.15	44.86	56.00	-11.14	QP	
12	3.6140	23.62	20.17	43.79	56.00	-12.21	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
 Operating Condition: Mode 1
 Test Specification: AC 230V, 50Hz for adapter
 Comment: Neutral Line
 Tem.: 22.8°C Hum.: 52%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1980	30.08	19.90	49.98	63.69	-13.71	QP	
2	0.4540	29.08	19.96	49.04	56.80	-7.76	QP	
3	0.4580	14.99	19.96	34.95	46.73	-11.78	AVG	
4	0.6340	7.98	20.02	28.00	46.00	-18.00	AVG	
5	0.8300	25.51	20.07	45.58	56.00	-10.42	QP	
6	1.1060	23.29	20.12	43.41	56.00	-12.59	QP	
7	1.2620	6.85	20.13	26.98	46.00	-19.02	AVG	
8	1.6180	4.78	20.13	24.91	46.00	-21.09	AVG	
9	1.7580	23.15	20.14	43.29	56.00	-12.71	QP	
10	2.3380	4.94	20.15	25.09	46.00	-20.91	AVG	
11	3.5740	3.33	20.17	23.50	46.00	-22.50	AVG	
12	3.6060	23.66	20.17	43.83	56.00	-12.17	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 110V, 50Hz for adapter
Comment: Live Line
Tem.: 22.8°C Hum.: 52%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1620	26.51	19.90	46.41	65.36	-18.95	QP	
2	0.3780	22.10	19.93	42.03	58.32	-16.29	QP	
3	0.4340	10.95	19.95	30.90	47.18	-16.28	AVG	
4	0.6460	18.86	20.02	38.88	56.00	-17.12	QP	
5	0.7740	6.80	20.06	26.86	46.00	-19.14	AVG	
6	1.1019	18.25	20.12	38.37	56.00	-17.63	QP	
7	1.2660	4.81	20.13	24.94	46.00	-21.06	AVG	
8	1.6860	16.24	20.13	36.37	56.00	-19.63	QP	
9	1.8540	4.30	20.14	24.44	46.00	-21.56	AVG	
10	2.4739	3.52	20.15	23.67	46.00	-22.33	AVG	
11	3.1619	17.09	20.16	37.25	56.00	-18.75	QP	
12	3.4940	2.29	20.17	22.46	46.00	-23.54	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 110V, 50Hz for adapter
Comment: Neutral Line
Tem.: 22.8°C Hum.: 52%



No.	Freq. (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit dBμV	Over Limit (dB)	Detector	Remark
1	0.1900	31.94	19.90	51.84	64.03	-12.19	QP	
2	0.1980	13.92	19.90	33.82	53.69	-19.87	AVG	
3	0.2540	27.09	19.89	46.98	61.62	-14.64	QP	
4	0.3820	28.42	19.93	48.35	58.23	-9.88	QP	
5	0.3820	13.73	19.93	33.66	48.23	-14.57	AVG	
6	0.4620	27.92	19.96	47.88	56.66	-8.78	QP	
7	0.7700	6.93	20.06	26.99	46.00	-19.01	AVG	
8	0.9020	25.51	20.09	45.60	56.00	-10.40	QP	
9	1.2620	21.07	20.13	41.20	56.00	-14.80	QP	
10	1.3940	4.69	20.13	24.82	46.00	-21.18	AVG	
11	1.9460	4.08	20.14	24.22	46.00	-21.78	AVG	
12	2.4580	4.15	20.15	24.30	46.00	-21.70	AVG	

3.2. Radiated Emission Test

3.2.1. Test Standard and Limit

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 8.2
Basic Standard	EN 55032: 2015

Radiated Emission Test Limit (Below 1000MHz)

Frequency (MHz)	Limit (dB μ V/m)	
	Quasi-peak Level	
	Class B	Class A
30MHz~230MHz	40	50
230MHz~1000MHz	47	57
Remark: 1. The lower limit shall apply at the transition frequency. 2. The test distance is 3m.		

Radiated Emission Test Limit (Above 1000MHz)

Frequency (MHz)	Limit (dB μ V/m)			
	Class B		Class A	
	Peak	Average	Peak	Average
1000 MHz -3000 MHz	70	50	76	56
3000 MHz -6000 MHz	74	54	80	60
Remark: 1. The lower limit applies at the transition frequency. 2. The test distance is 3m.				

Radiated Emission Test Limit for FM Receivers

Frequency (MHz)	Limit (dB μ V/m)	
	Quasi-peak Level	
	Fundamental	Harmonics
30MHz~230MHz	60	52
230MHz~300MHz	60	52
300MHz~1000MHz	60	56
Remark: 1. The lower limit shall apply at the transition frequency. 2. The test distance is 3m.		

Frequency Range of Radiated Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000

Above 1000

5th harmonic of the highest frequency or 6 GHz, whichever is lower

3.2.2. Test Setup




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

3.2.3. Test Procedure

- 1) The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- 2) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter test site. The table was rotated 360 degrees to determine the position of the highest radiation.

3) The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

4) The initial step in collecting radiated emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

5) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

The test receiver/spectrum was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.

6) For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.

The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak/ Average detection at frequency above 1GHz.

3.2.4. Test Data

PASS

The EUT should be compliance to the limit of Class B

Only the worst case data was showed in the report, please to see the following pages

Report No.: SZAWW190402002-01E

Page 25 of 75

Test Results (30~1000MHz)


Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH) 23.5°C/52%RH

Standard: EN301489_Class
B_3mPower Source: AC 230V, 50Hz for
adapter

Test Mode: Mode 1

Polarization: Horizontal




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.6340	37.33	-18.92	18.41	40.00	-21.59	peak			
2	851.0353	33.55	-6.75	26.80	47.00	-20.20	peak			
3	881.4067	33.95	-6.24	27.71	47.00	-19.29	peak			
4	925.7563	32.69	-5.58	27.11	47.00	-19.89	peak			
5	958.7943	33.55	-5.13	28.42	47.00	-18.58	peak			
6	993.0113	32.62	-4.62	28.00	47.00	-19.00	peak			

Test Results (30~1000MHz)

Job No.: SZAWW190402002
 Temp.(°C)/Hum.(%RH) 23.5°C/52%RH

Standard: EN301489_Class B_3m
 Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 1
 Polarization: Vertical



Report No.: SZAWW190402002-01E

Page 27 of 75

Test Results (30~1000MHz)


Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH) 23.5°C/52%RH

Standard: EN301489_Class
B_3mPower Source: AC 110V, 50Hz for
adapter

Test Mode: Mode 1

Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.4059	38.82	-18.92	19.90	40.00	-20.10	peak			
2	100.5806	41.41	-22.88	18.53	40.00	-21.47	peak			
3	771.4486	32.59	-8.15	24.44	47.00	-22.56	peak			
4	893.8567	33.55	-6.04	27.51	47.00	-19.49	peak			
5	938.8326	33.99	-5.41	28.58	47.00	-18.42	peak			
6	982.6200	33.04	-4.77	28.27	47.00	-18.73	peak			


Test Results (30~1000MHz)

Job No.:
 Standard:
 Test Mode:

SZAWW190402002
 EN301489_Class
 B_3m
 Mode 1

Temp.(°C)/Hum.(%RH):
 Power Source:
 Polarization:

23.5°C/52%RH
 AC 110V, 50Hz for
 adapter
 Vertical



Test Results (1GHz~6GHz)

Frequency (MHz)	Read Level (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector
1490.19	46.70	-2.67	44.04	70.00	-25.96	H	PEAK
1966.11	49.68	-3.11	46.57	70.00	-23.43	H	PEAK
1908.79	46.21	-4.57	41.64	70.00	-28.36	H	PEAK
4130.56	53.57	-4.48	49.08	74.00	-24.92	H	PEAK
4559.29	47.41	-5.13	42.29	74.00	-31.71	H	PEAK
5189.53	53.97	-5.21	48.76	74.00	-25.24	H	PEAK
1490.19	39.79	-2.67	37.13	50.00	-12.87	H	AVG
1966.11	44.19	-3.11	41.08	50.00	-8.92	H	AVG
1908.79	39.11	-4.57	34.54	50.00	-15.46	H	AVG
4130.56	45.18	-4.48	40.70	54.00	-13.30	H	AVG
4559.29	37.93	-5.13	32.80	54.00	-21.20	H	AVG
5189.53	38.71	-5.21	33.50	54.00	-20.50	H	AVG
1516.54	48.06	-2.58	45.48	70.00	-24.52	V	PEAK
2003.20	54.03	-2.48	51.55	70.00	-18.45	V	PEAK
2203.13	48.73	-4.30	44.42	70.00	-25.58	V	PEAK
4142.86	55.08	-4.70	50.38	74.00	-23.62	V	PEAK
4568.72	50.53	-5.17	45.36	74.00	-28.64	V	PEAK
5093.48	46.71	-5.97	40.74	74.00	-33.26	V	PEAK
1516.54	42.07	-2.58	39.49	50.00	-10.51	V	AVG
2003.20	40.56	-2.48	38.08	50.00	-11.92	V	AVG
2203.13	40.68	-4.30	36.38	50.00	-13.62	V	AVG
4142.86	42.09	-4.70	37.40	54.00	-16.60	V	AVG
4568.72	44.21	-5.17	39.04	54.00	-14.96	V	AVG
5093.48	37.61	-5.97	31.65	54.00	-22.35	V	AVG

Remark:


1. Level =Receiver Read level + Antenna Factor

3.3. Harmonic Current Emissions

3.3.1. Test Standard and Limit

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 8.5
Basic Standard	EN 61000-3-2: 2014
Test Limit	Please to refer to the clause 7 of standard EN 61000-3-2: 2014.

3.3.2. Test Setup



3.3.3. Test Procedure

- 1) The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions.
- 2) The classification of EUT is according to section 5 of EN 61000-3-2: 2014.The EUT is classified as follows:
Class A: Balanced three-phase equipment, Household appliances excluding equipment as Class D, Tools excluding portable tools, Dimmers for incandescent lamps, audio equipment, equipment not specified in one of the three other classes.
Class B: Portable tools; Arc welding equipment which is not professional equipment.
Class C: Lighting equipment.
Class D: Equipment having a specified power less than or equal to 600W of the following types: Personal computers and personal computer monitors and television.
- 3) The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.
- 4) For the actual test configuration, please refer to the related item –EUT Test Photos.

3.3.4. Test Data

The active input power of the EUT is less than 75W. Therefore, according to EN 61000-3-2, no limits are necessary.



3.4. Voltage Fluctuations and Flicker


3.4.1. Test Standard and Limit

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 8.6
Basic Standard	EN 61000-3-3: 2013

Voltage Fluctuation and Flicker Test Limit

Test Items	Limits
Pst	1.0
Plt	0.65
dc	3.3%
dmax	4.0%
dt	Not exceed 3.3% for 500ms

3.4.2. Test Setup



3.4.3. Test Procedure

- 1) Tests was performed according to the Test Conditions/Assessment of Voltage Fluctuations specified in Clause 5.0/6.0 of IEC555-3 and/or Clause 6.0/4.0 of IEC/EN 61000-3-3 depend on which standard adopted for compliance measurement.
- 2) All types of harmonic current and/or voltage fluctuation in this report are assessed by direct measurement using flicker-meter.
- 3) For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.4.4. Test Data

Please to see the following pages

Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH): 24.3°C/55%RH


Standard: EN 61000-3-3

Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 1

EMC PARTNER AG , Laufen

Flicker Emission IEC 61000-4-15 for 230V/50Hz



Actual Flicker (Fli): 0.00

Short-term Flicker (Pst): 0.07

Limit (Pst): 1.00

Long-term Flicker (Plt): 0.07

Limit (Plt): 0.65

Maximum Relative Volt. Change (dmax): 0.00%

Limit (dmax): 4.00%

Relative Steady-state Voltage Change (dc): 0.01%

Limit (dc): 3.00%

Tmax 3.30% (dt): 0.00ms

Limit (dt>Lim): 500ms

Flicker Emission - IEC 61000-3-3, EN 61000-3-3

Urms = 229.5 V P = 1.871 W

Irms = 0.023 A pf = 0.355

Range: 0.25 A

V-nom: 230 V

Test aborted, Result: PASSED

HAR-1000 EMC-Partner

Full Bar : Actual Values

Empty Bar : Maximum Values

Circles : Average Values

Blue : Current , Green : Voltage , Red : Failed

Measurement

EMC PARTNER AG , Laufen

Date : 2019/4/12 9:44:43 V4.22

File :

Operator

Jason Chen

Unit

SZAWW190402002

Serial Number

USR-G781

Remarks

Urms = 229.5V Freq = 50.000 Range: 0.25 A

Irms = 0.023A IpK = 0.146A cf = 6.356

P = 1.871W S = 5.267VA pf = 0.355

Test - Time : 1 x 10min = 10min (100 %)

LIN (Line Impedance Network) : L: 0.24ohm +j0.15ohm N: 0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.00 %
dtLim: 3.30 % dt>Lim: 500ms

Test aborted, Result: PASSED

	dmax	dc	dt>Lim
	[%]	[%]	[ms]
1	0.000	0.010	0.000

Definitions of Abbreviations

Urms *** Actual total Voltage in Volt RMS
Irms *** Actual total Current in Ampere RMS
Ipk *** Actual Peak value of the Current in Ampere
cf *** Actual Crest Factor (Ipk/Irms)
P *** Actual Active Power in Watt
S *** Actual Apparent Power in VA (Urms*Irms)
pf *** Actual Power Factor (P/S)

Plt Long term Flicker over all Pst cycles

For every Pst-cycle:

dmax Maximum voltage changes between two steady state conditions
dc Voltage changes between two steady conditions
dt>Lim Time during the voltage variation go to across
the defined limit (dtlim)

General :

- The values marked with "****" are actual values which could vary during test-time and are taken at the time of protocol printout.

4. Immunity Test

General Performance Criteria

◆ Performance criteria for continuous phenomena applied to transmitters and receivers (CT/CR)

During and after the test, the apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a permissible performance level specified by the manufacturer when the apparatus is used as intended. In some cases this permissible performance level may be replaced by a permissible loss of performance.

During the test the EUT shall not unintentionally transmit or change its actual operating state and stored data.

If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be deduced from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

◆ Performance criteria for transient phenomena applied to transmitters and receivers (TT/TR)

After the test, the apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a permissible performance level specified by the manufacturer, when the apparatus is used as intended. In some cases this permissible performance level may be replaced by a permissible loss of performance.

During the EMC exposure to an electromagnetic phenomenon, a degradation of performance is, however, allowed. No change of the actual mode of operation (e.g. unintended transmission) or stored data is allowed.

If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be deduced from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

◆ Performance criteria for equipment which does not provide a continuous communication link

For radio equipment which does not provide a continuous communication link, the performance criteria described in CT/CR and TT/TR are not appropriate, then the manufacturer shall declare, for inclusion in the test report, his own specification for an acceptable level of performance or degradation of performance during and/or after the immunity tests.

The performance criteria specified by the manufacturer shall give the same degree of immunity protection as called for in CT/CR and TT/TR.

◆ Performance criteria for ancillary equipment tested on a stand alone basis

If ancillary equipment is intended to be tested on a stand alone basis, the performance criteria described in CT/CR and TT/TR are not appropriate, then the manufacturer shall declare, for inclusion in the test report, his own specification for an acceptable level of performance or degradation of performance during and/or after the immunity tests.


The performance criteria specified by the manufacturer shall give the same degree of immunity protection as called for in CT/CR and TT/TR.

4.1. Electrostatic Discharge Test

4.1.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.3/EN 55035 Clause 4.2.1
Basic Standard	EN 61000-4-2:2009
Discharge Impedance:	330 ohm / 150 pF
Performance Criterion:	CT/CR
Discharge Voltage:	Air Discharge: 2kV/4kV/8kV
Polarity:	Positive & Negative
Number of Discharge:	Air Discharge: min. 20 times at each test point
Discharge Mode:	Single Discharge
Discharge Period:	1 second minimum

4.1.2. Test Setup



Note:

TABLE-TOP EQUIPMENT:

The configuration consisted of a wooden table 0.8 meters high standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A Horizontal Coupling Plane (1.6m x 0.8m) was placed on the table and attached to the GRP by means of a cable with 940kohm total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC /EN 61000-4-2, and its cables were placed on the HCP and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic

structure.

FLOOR-STANDING EQUIPMENT:

The equipment under test was installed in a representative system as described in section 7 of IEC/EN 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.

4.1.3. Test Procedure

The test generator necessary to perform direct and indirect application of discharges to the EUT in the following manner:

1) Contact discharge was applied to conductive surfaces and coupling planes of the EUT.

During the test, it was performed with single discharges. For the single discharge time between successive single discharges was at least 1 second.

Vertical Coupling Plane (VCP):

The coupling plane, of dimensions 0.5m x 0.5m, is placed parallel to, and positioned at a distance 0.1m from, the EUT, with the Discharge Electrode touching the coupling plane.

The four faces of the EUT will be performed with electrostatic discharge.

Horizontal Coupling Plane (HCP):

The coupling plane is placed under to the EUT. The generator shall be positioned vertically at a distance of 0.1m from the EUT, with the Discharge Electrode touching the coupling plane.

The four faces of the EUT will be performed with electrostatic discharge.

2) Air discharges at insulation surfaces of the EUT.

It was at least ten single discharges with positive and negative at the same selected point.

3) For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4. Test Data

Job No.:	SZAWW190402002	Temp.(°C)/Hum. (%RH):	24.3°C/55%RH
Standard:	EN61000-4-2	Power Source:	AC 230V, 50Hz for adapter
Test Mode:	All Mode		

Item	Contact Discharge to conducted surfaces and to coupling planes		Air Discharge at insulating surfaces
	Direct Contact Discharge	Indirect Contact Discharge	
Test Voltage	Reaction of EUT / Result	Reaction of EUT / Result	Reaction of EUT / Result
+2kV	n.r.r. PASS	n.r.r. PASS	n.r.r. PASS
-2kV	n.r.r. PASS	n.r.r. PASS	n.r.r. PASS
+4kV	n.r.r. PASS	n.r.r. PASS	n.r.r. PASS
-4kV	n.r.r. PASS	n.r.r. PASS	n.r.r. PASS

+6kV	-	-	n.r.r. PASS
-6kV	-	-	n.r.r. PASS
+8kV	-	-	n.r.r. PASS
-8kV	-	-	n.r.r. PASS

Remarks: n.r.r. = no reaction recognized


Performance Criteria A observed and No any function degraded during the tests.

4.2. Radiated, RF Electromagnetic Fields Test

4.2.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.2/EN 55035 Clause 5
Basic Standard	EN 61000-4-3: 2006+A1:2008+A2:2010
Required Performance	A
Frequency Range	80MHz to 6GHz
Field Strength	3 V/m
Modulation	1kHz Sine Wave, 80%, AM Modulation
Frequency Step	1 % of preceding frequency value
Polarity of Antenna	Horizontal and Vertical
Test Distance	3 m
Antenna Height	1.5 m
Dwell Time	at least 3 seconds

4.2.2. Test Setup



4.2.3. Test Procedure

The EUT and support equipment, which are placed on a table that is 0.8 meter above ground and the testing was performed in a fully-anechoic chamber. The testing distance from antenna to the EUT was 3 meters.

- 1) The field strength level was 3V/m

- 2) The frequency range is swept from 80 MHz to 6000 MHz with the signal 80%amplitude modulated with a 1kHz sine wave.
- 3) The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond, but shall in no case be less than 0.5s.
- 4) The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

4.2.4. Test Data

Job No.: SZAWW190402002 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
Standard: EN61000-4-3 Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 1

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Observation	Perform. Criteria	Results
80~6000	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	CT,CR	A	PASS
			Rear			
			Left			
			Right			

Job No.: SZAWW190402002 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
Standard: EN61000-4-3 Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 2

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Observation	Perform. Criteria	Results
80~6000	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	CT,CR	A	PASS
			Rear			

			Left			
			Right			

Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: EN61000-4-3

Power Source: AC 230V, 50Hz for adapter/

Test Mode: Mode 3

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Observation	Perform. Criteria	Results
80~6000	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	CT,CR	A	PASS
			Rear			
			Left			
			Right			

Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: EN61000-4-3

Power Source: AC 230V, 50Hz for adapter/

Test Mode: Mode 4

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Observation	Perform. Criteria	Results
-----------------------	-------------------	---------------------	---------	-------------	-------------------	---------

80~6000	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	CT,CR	A	PASS
			Rear			
			Left			
			Right			

Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: EN61000-4-3

Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 5

Frequency Range (MHz)	RF Field Position	R.F. Field Strength	Azimuth	Observation	Perform. Criteria	Results
80~6000	H / V	3 V/m (rms) AM Modulated 1000Hz, 80%	Front	CT,CR	A	PASS
			Rear			
			Left			
			Right			

EUT operating Mode		Polarity	Position (°)	Max. value	Frequency (MHz)
Call Mode(GSM900)	Uplink	H	Front	-40.76	372.18
		V	Front	-42.01	757.06
	Downlink	H	Front	-81.87	864.64
		V	Front	-82.77	876.04
	RX Quality	H	Front	0	80.00
		V	Front	0	80.00

Note: DownLink SPL = 0 dBPa at 1KHz at the input of acoustic coupler
Uplink SPL = -5 dBPa at 1KHz at the Mouth Reference Point

EUT operating Mode		Polarity	Position (°)	Max. value	Frequency (MHz)
Call Mode(WCDMA900)	Uplink	H	Front	-41.74	372.17
		V	Front	-43.96	756.64
	Downlink	H	Front	-83.51	864.40
		V	Front	-83.98	875.31
	RX Quality	H	Front	0	80.00
		V	Front	0	80.00

Note: DownLink SPL = 0 dBPa at 1KHz at the input of acoustic coupler
Uplink SPL = -5 dBPa at 1KHz at the Mouth Reference Point

EUT operating Mode		Polarity	Position (°)	Throughput(95%)
Data Mode (LTEB1)	Uplink	H	Front	≥ 95
		V	Front	≥ 95
	Downlink	H	Front	≥ 95
		V	Front	≥ 95


All supported band has been tested, only worst data listed.

4.3. Fast Transients, Common Mode Test

4.3.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.4/EN 55035 Clause 4.2.4
Basic Standard	EN 61000-4-4:2012
Required Performance	B
Test Voltage:	Power Line: 1 kV
Polarity:	Positive & Negative
Impulse Frequency:	5 kHz
Impulse Wave shape :	Tr/Th 5/50 ns
Burst Duration:	15 ms for 5KHz Repetition Frequency
Burst Period:	300 ms
Test Duration	1 min

4.3.2. Test Setup



Note: (A) location for supply line coupling

(B) location for signal lines coupling

For the actual test configuration, please refer to the related item – Photographs of the Test Setup

4.3.3. Test Procedure

The EUT and support equipment, are placed on a table that is 0.8 meter above a metal ground plane measured 1m*1m min. and 0.65mm thick min.

The other condition as following manner:

Shenzhen Anbotek Compliance Laboratory Limited

Code:AB-RF-04-a

Address: 1/F, Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel: (86)755-26066440 Fax: (86)755-26014772 Email: service@anbotek.com



Hotline

400-003-0500

www.anbotek.com

- 1) The distance between any coupling devices and the EUT should be (0.5-0/+0.1)m for table-top equipment testing, and (1.0±0.1)m for floor standing equipment.
- 2) Both positive and negative polarity discharges were applied.
- 3) The duration time of each test sequential was 1 minute
- 4) For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.3.4. Test Data

Job No.:	SZAWW190402002	Temp.(°C)/Hum.(%RH)	24.3°C/55%RH
Standard:	EN61000-4-4	Power Source:	AC 230V, 50Hz for adapter
Test Mode:	Mode 1		

Coupling Line		Test level (kV)								Observation	Criterion	Results
		0.5		1		2		4				
		+	-	+	-	+	-	+	-			
AC Line	L	P	P	P	P					TT,TR	B	PASS
	N	P	P	P	P							PASS
	L+N	P	P	P	P							PASS


Note: 1)There was not any unintentional transmission in standby mode
 2) In the table: 'P' represents 'PASS'; 'F' represents 'FAIL'.

4.4. Surges Test

4.4.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.8/EN 55035 Clause 4.2.5
Basic Standard	EN 61000-4-5:2014
Required Performance	B
Wave-Shape:	Combination Wave
Test Voltage:	Line to Line: 1 kV; Line to ground: 2kV
Generator Source:	2 ohm between networks
Impedance:	12 ohm between network and ground
Polarity:	Positive/Negative
Phase Angle:	0°/90°/180°/270°
Pulse Repetition Rate:	1 time / min. (maximum)
Number of Tests:	5 positive and 5 negative at selected points

4.4.2. Test Setup



4.4.3. Test Procedure

1) For EUT power supply:

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall be 2meters in length (or shorter).

For double-insulated products without PE or external earth connections, the test shall be done in a similar way as for grounded products but without adding any additional external grounded connections. If there are no other possible connections to earth, line-to-ground tests may be omitted.

2) For Unshielded unsymmetrical interconnection lines:

The surge is applied to the lines via the capacitive coupling. The coupling /decoupling networks shall not influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length.

3) Unshielded symmetrical interconnections communication lines:

The surge is applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor cannot be specified. The interconnection line between the EUT and the coupling/decoupling networks shall be 2 meters in length.

4) For Shielded lines:

Direct application,

The EUT is isolated from ground and the surge is applied to its metallic enclosure; the termination (or auxiliary equipment) at the port(s) under test is grounded. This test applies to equipment with single or multiple shielded cables.

Rules for application of the surge to shielded lines:

i) Shields grounded at both ends

> The surge injection on the shield.

ii) Shields grounded at one end

> If in the installation the shield is connected only at the auxiliary equipment, test shall be done in that configuration but with the generator still connected to the EUT side. If cable lengths allow, the cables shall be on insulated supports 0.1 m above the ground plane or cable tray.

For products which do not have metallic enclosures, the surge is applied directly to the shielded cable.

- Alternative coupling method for testing single cables in a multi-shield configuration, Surges are applied in close proximity to the interconnection cable under test by a wire. The length of the cable between the port(s) under test and the device attached to the other end of the cable shall be the lesser of the maximum length permitted by the EUT's specification, or 20 m. Where the length exceeds 1 m, excess lengths of cables shall be bundled at the approximate centre of the cables with the bundles 30 cm to 40 cm in length.

4.4.4. Test Data



Job No.: SZAWW190402002

Temp.(°C)/Hum.(%RH): 24.3°C/55%RH

Standard: EN61000-4-5

Power Source: AC 230V, 50Hz for adapter

Test Mode: Mode 1

Coupling Line			Test level								Observation	Criterion	Result
			0.5 kV		1 kV		2 kV		4 kV				
			+	-	+	-	+	-	+	-			
AC line	L-N	0°	P	P	P	P					TT,TR	B	PASS
		90°	P	P	P	P							
		180°	P	P	P	P							
		270°	P	P	P	P							

Note: 1) There was not any unintentional transmission in standby mode


2) In the table: 'P' represents 'PASS'; 'F' represents 'FAIL'.

4.5. Radio Frequency, Common Mode Test

4.5.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.5/EN 55035:2017 Clause 5
Basic Standard	EN 61000-4-6:2014
Required Performance	A
Frequency Range:	0.15 MHz - 80 MHz/0.15MHz~10MHz, 10MHz~30MHz, 30MHz~80MHz
Field Strength:	3 Vr.m.s./3V~1Vr.m.s./3Vr.m.s.
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of fundamental
Dwell Time:	at least 3 seconds

4.5.2. Test Setup



4.5.3. Test Procedure

- 1) The EUT was placed on an insulating support of 0.1m height above a ground reference Plane, arranged and connected to satisfy its functional requirement. All cables exiting the EUT was supported at a height of at least 30 mm above the ground reference plane.
- 2) The coupling and decoupling devices were required, they were located between 0.1 m and 0.3 m from the EUT. This distance was to be measured horizontally from the projection of the EUT on to the ground reference plane to the coupling and decoupling device.

3) Each AE, used with clamp injection, shall be placed on an insulating support 0.1 m above the ground reference plane. A decoupling network shall be installed on each cable between the EUT and AE except the cable under test. All cables connected to each AE, other than those being connected to the EUT, shall be provided with decoupling networks. The decoupling networks connected to each AE (except those on cables between the EUT and AE) shall be applied no further than 0.3 m from the AE. The cable(s) between the AE and the decoupling network (s) or in between the AE and the injection clamp shall not be bundled nor wrapped and shall be kept between 30 mm and 50 mm above the ground reference plane.

4) The frequency range was swept from 150 kHz to 230 MHz, using the signal levels established during the setting process, and with the disturbance signal 80% amplitude modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or to change coupling devices as necessary. Where the frequency was swept incrementally, the step size do not exceed 1% of the preceding frequency

4.5.4. Test Data

Job No.: SZAWW190402002 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
 Standard: EN61000-4-6 Power Source: AC 230V, 50Hz for adapter
 Test Mode: All Mode

Voltage (V)	Test Frequency (MHz)	Tested Line	Injection Method.	Performance Criterion	Test Result
3	0.15 – 80	AC line	CDN-M2	CT/CR	PASS

Remark: For normal operating function: There was no change compared with the initial operation during and after the test.

Job No.: SZAWW190402002 Temp.(°C)/Hum.(%RH): 24.3°C/55%RH
 Standard: EN61000-4-6 Power Source: AC 230V, 50Hz for adapter
 Test Mode: Mode 1~Mode 10

Voltage (V)	Test Frequency (MHz)	Tested Line	Injection Method.	Performance Criterion	Test Result
3	0.15 – 10	AC line	CDN-M2	CT/CR	PASS
3~1	10~30	AC line	CDN-M2	CT/CR	PASS
3	30~80	AC line	CDN-M2	CT/CR	PASS

Remark: For normal operating function: There was no change compared with the initial operation during and after the test.

EUT operating Mode		Max. value	Frequency (MHz)
Call Mode(GSM900)	Uplink	-49.44	25.06
		-49.99	58.60
	Downlink	-62.71	28.18
		-63.49	35.66
	RX Quality	0	80.00
		0	80.00

Note: DownLink SPL = 0 dBPa at 1KHz at the input of acoustic coupler
Uplink SPL = -5 dBPa at 1KHz at the Mouth Reference Point

EUT operating Mode		Max. value	Frequency (MHz)
Call Mode(WCDMA900)	Uplink	-50.39	25.95
		-50.98	59.25
	Downlink	-64.66	27.69
		-66.14	36.12
	RX Quality	0	80.00
		0	80.00

Note: DownLink SPL = 0 dBPa at 1KHz at the input of acoustic coupler
Uplink SPL = -5 dBPa at 1KHz at the Mouth Reference Point

EUT operating Mode		Position(MHz)	Throughput(95%)
Data Mode (LTEB1)	Uplink	12.5	≥ 95
	Downlink	15.1	≥ 95
Data Mode (LTEB3)	Uplink	13.6	≥ 95
	Downlink	15.4	≥ 95


Data Mode (LTEB8)	Uplink	13.8	≥ 95
	Downlink	14.7	≥ 95
Data Mode (LTEB38)	Uplink	13.5	≥ 95
	Downlink	14.9	≥ 95
Data Mode (LTEB40)	Uplink	12.9	≥ 95
	Downlink	16.3	≥ 95

4.6. Voltage Dips and Interruptions

4.6.1. Test Standard and Specification

Test Standard	ETSI EN 301 489-1 V2.1.1 Clause 9.7/EN 55035:2017 Clause 4.2.6
Basic Standard	EN 61000-4-11:2004
Voltage Dips:	0% reduction, 0.5 Cycle
Voltage Interruptions:	0% reduction, 250 Cycles
Interval between Event:	Minimum 10 seconds
Phase Angle:	0°/180°
Test Cycle:	3 times

4.6.2. Test Setup



4.6.3. Test Procedure

- 1) The EUT was placed on a ground reference plane(GRP)insulated by an insulating support 0,1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
2. The test was performed with the EUT connected to the test generator with the shortest power supply cable as specified by the EUT manufacturer.
3. The EUT was tested for each selected combination of test level and duration with a sequence of three dips/interruptions with intervals of 10 s minimum. Each representative mode of operation was tested.
4. For EUT with more than one power cord, each power cord was tested individually.

4.6.4. Test Data

Job No.: SZAWW190402002 Temp.(°C)/Hum. (%RH) 24.3°C/55%RH
Standard: EN61000-4-11 Power Source: AC 230V, 50Hz for adapter
Test Mode: Mode 1

Ut:230Vac 50Hz	Durations		Event interval (sec)	Total events (time)	Performance Criterion	Result
Voltage residual (%)	(period)	(ms)	10	3	TT/TR	PASS
0	1	20	10	3	TT/TR	PASS
0	0.5	10	10	3	TT/TR	PASS
70	25	500	10	3	TT/TR	PASS
0	250	5000	10	3	TT/TR	PASS
70	0.5	10	10	3	TT or CR	PASS

Ut:100Vac 50Hz	Durations		Event interval (sec)	Total events (time)	Performance Criterion	Result
Voltage residual (%)	(period)	(ms)	10	3	TT/TR	PASS
0	1	20	10	3	TT/TR	PASS
0	0.5	10	10	3	TT/TR	PASS
70	25	500	10	3	TT/TR	PASS
0	250	5000	10	3	TT/TR	PASS
70	0.5	10	10	3	TT or CR	PASS

Ut:240Vac 50Hz	Durations		Event interval (sec)	Total events (time)	Performance Criterion	Result
Voltage residual (%)	(period)	(ms)	10	3	TT/TR	PASS
0	1	20	10	3	TT/TR	PASS
0	0.5	10	10	3	TT/TR	PASS
70	25	500	10	3	TT/TR	PASS
0	250	5000	10	3	TT/TR	PASS
70	0.5	10	10	3	TT or CR	PASS

APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Test




Photo of Radiation Emission Test




Photo of Flicker Test




Photo of Electrostatic Discharge Test



Photo of RF Field Strength Susceptibility Test




Photo of Electrical Fast Transient /Burst Immunity Test





Photo of Surge Test



Photo of Dips Immunity Test



Photo of C/S Test



APPENDIX II -- EXTERNAL PHOTOGRAPH







Anbotech

Product Safety

安博检测

Anbotech Testing

Report No.: SZAWW190402002-01E

Page 65 of 75



Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-04-a

Address: 1/F, Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel: (86)755-26066440 Fax: (86)755-26014772 Email: service@anbotech.com





Hotline



400-003-0500



www.anbotech.com



APPENDIX III -- INTERNAL PHOTOGRAPH
































----- End of Report -----

Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-04-a

Address: 1/F, Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)755-26066440 Fax: (86)755-26014772 Email: service@anbotech.com

 **Hotline**
400-003-0500
www.anbotech.com