

# TEST REPORT

**Applicant:** Jinan USR IOT Technology Limited

**Address of Applicant:** Floor 2, Wuzhou Scientific Research Building, No.1100  
Shunfeng Street, Gaoxin District, Jinan, Shandong, China

**Equipment Under Test (EUT)**

Product Name: LoRa Converter

Model No.: USR-LG206, USR-LG201, USR-LG202, USR-LG203, USR-LG204, USR-LG205, USR-LG207, USR-LG208, USR-LG209

**Applicable standards:** EN 62311:2008

**Date of sample receipt:** 10 Aug., 2018

**Date of Test:** 13 Aug., to 12 Dec., 2018

**Date of report issue:** 13 Dec., 2018

**Test Result:** PASS\*

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The protection requirements with respect to electromagnetic compatibility contained in Directive 1999/5/EC are considered.



Bruce Zhang  
Laboratory Manager



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	13 Dec., 2018	Original

**Tested by:**

*Zora Lee*

**Date:**

13 Dec., 2018

**Test Engineer**

**Reviewed by:**

*Wimer Zhang*

**Date:**

13 Dec., 2018

**Project Engineer**

## 3 Contents

Page

1	COVER PAGE.....	1
2	VERSION .....	2
3	CONTENTS .....	3
4	GENERAL INFORMATION.....	4
4.1	CLIENT INFORMATION .....	4
4.2	GENERAL DESCRIPTION OF E.U.T. ....	4
4.3	OPERATING MODES .....	4
4.4	DESCRIPTION OF SUPPORT UNITS.....	4
4.5	LABORATORY FACILITY .....	4
4.6	LABORATORY LOCATION .....	4
4.7	TEST INSTRUMENTS LIST.....	5
5	TECHNICAL REQUIREMENTS SPECIFICATION IN EN 62311 .....	6
5.1	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	6
5.2	RF EXPOSURE EVALUATION.....	6
5.2.1	Limit.....	6
5.2.2	Test method .....	6
5.2.3	Measurement data: .....	7
5.2.4	Conclusion.....	7

## 4 General Information

### 4.1 Client Information

Applicant:	Jinan USR IOT Technology Limited
Address:	Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, China
Manufacturer/Factory:	Jinan USR IOT Technology Limited
Address:	Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street, Gaoxin District, Jinan, Shandong, China

### 4.2 General Description of E.U.T.

Product Name:	LoRa Converter
Model No.:	USR-LG206, USR-LG201, USR-LG202, USR-LG203, USR-LG204, USR-LG205, USR-LG207, USR-LG208, USR-LG209
Hardware version:	V1.2
Software version:	V1.0.3
Modulation:	Lora
Antenna type:	External Antenna
Antenna Gain:	1.4 dBi

### 4.3 Operating Modes

Operating mode	Detail description
Transmitting mode	Keep the TX unit in transmitting mode with modulation

### 4.4 Description of Support Units

N/A
-----

### 4.5 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>● <b>FCC - Registration No.: 727551</b> Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.</li> <li>● <b>IC - Registration No.: 10106A-1</b> The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.</li> <li>● <b>CNAS - Registration No.: CNAS L6048</b> Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.</li> <li>● <b>A2LA - Registration No.: 4346.01</b> This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <a href="https://portal.a2la.org/scopepdf/4346-01.pdf">https://portal.a2la.org/scopepdf/4346-01.pdf</a></li> </ul>
---

### 4.6 Laboratory Location

<p>Shenzhen Zhongjian Nanfang Testing Co., Ltd. Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755-23118282 Fax: +86-755-23116366</p>
---

## 4.7 Test Instruments list

Conducted method:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Agilent	N9020A	MY50510123	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Vector Signal Generator	Agilent	N5182A	MY49060014	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Signal Generator	R&S	SMR20	1008100050	03-07-2018	03-06-2019
Power Sensor	D.A.R.E	RPR3006W	15I00041SNO12	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Power Sensor	D.A.R.E	RPR3006W	15I00041SNO54	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Power Sensor	D.A.R.E	RPR3006W	17I00015SNO27	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Power Sensor	D.A.R.E	RPR3006W	17I00015SNO28	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
RF Switch Unit	Ascentest	AT890-RFB	N/A	N/A	N/A
Test Software	MWRFTEST	MTS 8310	Version: 2.0.0.0		

## 5 Technical Requirements Specification in EN 62311

### 5.1 General Description of Applied Standards

EN 62311 Generic standard to demonstrate the compliance of electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (0 Hz–300 GHz) is to demonstrate the compliance of apparatus with the basic restrictions or reference levels on exposure of the general public related to electric, magnetic, electromagnetic fields as well as induced and contact current.

### 5.2 RF Exposure Evaluation

#### 5.2.1 Limit

Reference levels for electric, magnetic and electromagnetic fields  
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	—	$3,2 \times 10^4$	$4 \times 10^4$	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375\ f^{1/2}$	$0,0037\ f^{1/2}$	$0,0046\ f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

1.  $f$  as indicated in the frequency range column.

#### 5.2.2 Test method

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. Warning statement of the user for keeping 20cm separation distance and the prohibition of operating to a person has been printed on the user manual. So, this product under normal use is located on electromagnetic far field between the human body.

##### Far Field Calculation Formula

$$E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

$G$  = antenna gain relative to an isotropic antenna  
 $\theta, \phi$  = elevation and azimuth angles to point of investigation  
 $r$  = distance from observation point to the antenna

## 5.2.3 Measurement data:

Frequency	Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	E Field Strength (V/m)	E Field Strength Limit (V/m)	Result
865.00	11.41	13.84	1.40	1.38	3.78	40.44	Pass
866.00	11.40	13.80	1.40	1.38	3.78	40.46	Pass
867.00	11.39	13.77	1.40	1.38	3.76	40.49	Pass
868.00	11.34	13.61	1.40	1.38	3.75	40.51	Pass
915.10	10.81	12.05	1.40	1.38	3.53	41.59	Pass

## 5.2.4 Conclusion

Meet the requirements of EN 62311:2008

-----End of report-----